



STEALTH TURBO SHIELD

RATED TO: 1800°F CONTINUOUS 2200°F INTERMITTENT

Keep cool, lay low with our Stealth Turbo Heat Shields, the black turbo heat shield you have been waiting for. Retaining heat inside the turbo can not only lower under hood temperatures up to 40%, but it can also reduce chatter, lag, increase boost (in some cases), and reduce radiant heat damage to other engine components. The custom fit turbo heat bags use the same extreme rated technology as our other turbo shields, but they have a new cool black "Stealth" appearance. Capable of withstanding 1800°F continuous, our turbo heat shields are designed for street performance and even the most hardcore racing applications. The custom fit design means you do not have to trim or fit the heat shield blanket to fit your turbo housings making installation a snap, turbo removal is not necessary in most cases, kit includes two stainless steel springs to be used with anchors to hold in place.



PART NO.	DESCRIPTION
300543	T3 Flange
300544	T4 Flange
300545	T4 Flange Mid-Frame/Large
300546	T6 Flange
300548	T2 Flange (G25,27,28) w/ wastegate
300550	Dodge Cummins 5.9L
300551	2003-2006 Mitsubishi 8/9 OEM

APPLICATIONS:



FEATURES:

- Continuous operating temperature of 1800°F, 2200°F intermittent
- Capable of reducing up to 60% of under hood heat
- Does not conduct heat like all metal turbo shields
- Reduces turbo lag, lowers under hood temperatures
- Custom fit installs in minutes
- Custom shields available, will require housing to make prototype
- Made in USA